

# SUBLIBLOCK® TURBO

White  
SB-3105-T

Red  
SB-3301-T

Orange  
SB-3333-T

Athletic Yellow  
SB-3426-T

Columbia Blue  
SB-3576-T

Antique Silver  
SB-3834-T

Old Gold  
SB-3843-T

Neon Pink  
SB-3910-T

Neon Yellow  
SB-3920-T

Neon Orange  
SB-3930-T

Neon Green  
SB-3940-T

- Reformulated for use with modern performance polyesters
- Low temperature prevents heat-press marks on polyester garments
- Has a soft hand, excellent opacity, and blocks dye-migration
- Pressure-sensitive carrier enables easy weeding and repositioning

## Acceptable Fabrics

Cotton, Uncoated Polyester, Fabric Blends, Spandex, Lycra, Wool, Linen  
**Excluding Nylon**

## Sizing Available

Available Widths (in.): 15" and 20"  
Available Lengths (ft.): 15', 30', 45', 60', and 90' rolls

## Thickness

5.2 mils/130 microns

## Special Precautions

**Do not pre-heat the garment. Do not roll this material up in the opposite direction that it came- it will lead to delamination lines. After cutting your design, do not leave hanging on the cutter. If bubbling around the cut lines appears- lay it out flat and smooth down the bubbles with your hand.**



**45° Blade  
Recommended**



**Cut this material  
in mirror image**



**270°F**



**Medium,  
even pressure**



**5 Seconds**



**Peel Warm**



**Wash inside-out,  
wash warm, tumble  
dry normal. Suitable  
for dry-cleaning.**



**SpecialtyMaterials.com | 877.437.8556**

**Specialty  
Materials™**

Test on dazzle cloth and other moisture-wicking polyesters. Moisture-wicking materials have better adhesion when washed and dried using no fabric softener or blotted with rubbing alcohol before pressing. Be advised that dye migration has occurred with low energy dyes in polyester and poly-blend fabrics. All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability, whatsoever, in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

**Copyright © 2022, Specialty Materials & Digital Decoration, LLC. All rights reserved. Tulsa, OK 74107 | 866-437-8599**