



DecoFILM® GLOSS



FABRICS

Cotton, Uncoated Polyester, Fabric Blends, and similar fabrics - **Excluding Nylon**

SIZING

Available Widths (in.): 12" and 20"
Available Lengths (ft.): (12") 30', 60', 90', & 162' only
(20") 15', 30', 45', 60', 90', & 162' rolls
Sheets: 1 2" x 15" | Packs of 10 and 20

THICKNESS

2.76 mils/70 microns

Eco-friendly polyurethane film that offers a luxurious shine.
Polished on the surface to give it a glossy look that can also be layered. Smooth, durable, and can be used to cut fine-detailed designs.
Pressure-sensitive carrier enables easy weeding and repositioning.

COLOR VARIATION: During the manufacturing process, color variation can occur between rolls. This is especially true for Neon colors.



- **CUTTING**
45° Blade Recommended



- **PRESSING**
Firm, even pressure



- **TIMING**
8 seconds



- **WASHING**
Wash inside-out, cold water, gentle cycle, tumble dry low.



- **MIRRORING**
Cut this material in mirror image.



- **TEMPERATURE**
284°F



- **PEELING**
Peel warm



- **LASER COMPATIBLE**
This product contains no PVC and will not emit hazardous fumes.

"It's best to test!" Pre-test on an inconspicuous area before applying final production. Some garments require pre-heating and treatment, such as blotting moisture-wicking material with rubbing alcohol, before pressing material. Dye migration may occur with low energy dyes in polyester and blend fabrics. Check for compatibility and pre-treatment suggestions with each product's instructions. The user assumes all risk and liability, whatsoever, in connection with the use of this product. Specialty Materials cannot guarantee performance for conditions not under manufacturer's control and is not responsible for issues due to third-party material qualities. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

©2022 Specialty Materials & Digital Decoration, LLC. | All rights reserved | Tulsa, OK 74107 | 877-437-8556

Tech Help: tech@specialtymaterials.com | Sample Request: samples@specialtymaterials.com