



# DecoFILM® Paint FX



CPSIA  
COMPLIANT

## FABRICS

Cotton, Uncoated Polyester, Fabric  
Blends, Spandex, Lycra, Wool, Linen -  
**Excluding Nylon**

## SIZING

Available Widths (in.): 15" and 20"  
Available Lengths (ft.): 15', 30', 45', 60', and  
90' rolls

## THICKNESS

4 mils/100 microns

Pearlescent transfer films that resemble the shimmer of new car paint. Easy to cut and weed.  
Can be used on sport and leisure wear. Pressure-sensitive carrier enables easy weeding and repositioning.

**COLOR VARIATION:** During the manufacturing process, color variation may occur between rolls.  
This is especially true for Neon colors.



### CUTTING

45° Blade Recommended



### PRESSING

Firm, even pressure



### TIMING

17-20 seconds



### WASHING

Wash inside out, cold water, gentle cycle.  
Dry low heat. Suitable for dry-cleaning.



### MIRRORING

Cut this material in mirror image.



### TEMPERATURE

310°F - 330°F



### PEELING

Peel warm, cover with Teflon™ sheet  
and re-press for 2 seconds.



### LASER COMPATIBLE

This product contains no PVC and will  
not emit hazardous fumes.

**"It's best to test!"** Pre-test on an inconspicuous area before applying final production. Some garments require pre-heating and treatment, such as blotting moisture-wicking material with rubbing alcohol, before pressing material. Dye migration may occur with low energy dyes in polyester and blend fabrics. Check for compatibility and pre-treatment suggestions with each product's instructions. The user assumes all risk and liability, whatsoever, in connection with the use of this product. Specialty Materials cannot guarantee performance for conditions not under manufacturer's control and is not responsible for issues due to third-party material qualities. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

©2022 Specialty Materials & Digital Decoration, LLC. | All rights reserved | Tulsa, OK 74107 | 877-437-8556  
Tech Help: [tech@specialtymaterials.com](mailto:tech@specialtymaterials.com) | Sample Request: [samples@specialtymaterials.com](mailto:samples@specialtymaterials.com)