

FASHION Flex® PUFF



COMPLIANT

FABRICS

Cotton, Uncoated Polyester, Fabric Blends, Polyester/Acrylic, and Similar Fabrics - **Excluding Nylon**

SIZING

Available Widths (in.): 19.5" only Available Lengths (ft.): 15', 30', 45', 60', and 81' rolls

THICKNESS

4.9-6.7 mils/125-170 microns

Puffs up when pressed - no need for re-pressing to get the puff effect. Easy to weed with simple application instructions. We offer the most Puff colors in the industry. Pressure-sensitive carrier enables easy weeding and repositioning.

Special Precautions: *Cannot be layered. Remove carrier immediately after pressing.

If the carrier or transfer sheet is left on, it can create inconsistencies in the puffed material.

Color Variation: PLEASE NOTE: These instructions have changed. Be sure to use the settings provided on your roll. Test before doing large runs.





CUTTING

45° Blade



PRESSING

Medium, even pressure



TIMING

12-14 seconds
*Start at 12, if more time is needed, press
for an additional 2 seconds.



WASHING

Wash inside-out, cold water, gentle cycle. Tumble dry low.



MIRRORING

Cut this material in mirror image.



TEMPERATURE

All colors: 255°F - 275°F *Vary the Puff effect by Increasing or decreasing temp by 10°F within range



PEELING

Peel hot - remove carrier and/or transfer sheet immediately.



LASER COMPATIBLE

This product contains no PVC and will not emit hazardous fumes.

"It's best to test!" Pre-test on an inconspicuous area before applying final production. Some garments require pre-heating and treatment, such as blotting moisture-wicking material with rubbing alcohol, before pressing material. Dye migration may occur with low energy dyes in polyester and blend fabrics. Check for compatibility and pre-treatment suggestions with each product's instructions. The user assumes all risk and liability, whatsoever, in connection with the use of this product.

Specialty Materials cannot guarantee performance for conditions not under manufacturer's control and is not responsible for issues due to third-party material qualities. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

©2022 Specialty Materials & Digital Decoration, LLC. | All rights reserved | Tulsa, OK 74107 | 877-437-8556 Tech Help: tech@specialtymaterials.com | Sample Request: samples@specialtymaterials.com