

REFLECTION DECORATION



COMPLIANT

FABRICS

Cotton, Uncoated Polyester, Fabric Blends, Lycra, Wool, Linen - **Excluding Nylon**

SIZING

Available Widths (in.): 19" only (Chameleon Reflective Black 17.5" only) Available Lengths (ft.): 15', 30', 45', 60', 75', 90', and 162' rolls

THICKNESS

Chameleon Black: 7.2 mils/180 microns RD (300 series): 7.5 mils/190 microns

Use for nighttime visibility and brilliance in the spotflight. Consists of very small glass beads that are embedded in a layer of polyester film.

RD 300 series: has sticky carrier and very easy to weed.

SPECIAL PRECAUTIONS: Will NOT stretch or layer. Please note: The darker the color, the lower the reflectivity.

COLOR VARIATION: During the manufacturing process, color variation can occur between rolls. This is especially true for Neon colors.

TECH TIPS: 300 Series and Chameleon Reflective Black: NO PROTECTIVE LINER TO REMOVE.





CUTTING

60° Blade Recommended (slow cutting speed)



PRESSING

Firm, even pressure



TIMING

Pre-press garment for 5 seconds, then press design for 3-5 seconds.



WASHING

300 Series & Chameleon Reflective Black - Wash inside-out. Warm water, normal cycle. No bleach. Not suitable for dry-cleaning or steam cleaning. Do not iron directly onto the reflective vinyl.



MIRRORING

Cut this material in mirror image.



TEMPERATURE

300 Series & Chameleon Reflective Black - 300°F



PEELING

300 Series & Chameleon Reflective Black - HOT!
(Wait 2-3 seconds then peel)



LASER COMPATIBLE

This product contains no PVC and will not emit hazardous fumes.

"It's best to test!" Pre-test on an inconspicuous area before applying final production. Some garments require pre-heating and treatment, such as blotting moisture-wicking material with rubbing alcohol, before pressing material. Dye migration may occur with low energy dyes in polyester and blend fabrics. Check for compatibility and pre-treatment suggestions with each product's instructions. The user assumes all risk and liability, whatsoever, in connection with the use of this product.

Specialty Materials cannot guarantee performance for conditions not under manufacturer's control and is not responsible for issues due to third-party material qualities. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.