



ThermoFlex® STRETCH



CPSIA
COMPLIANT

FABRICS

Cotton, Uncoated Polyester, Fabric Blends, Spandex, Lycra, Wool, Linen -
Excluding Nylon

SIZING

Available Widths (in.): 15" and 20"
Available Lengths (ft.): 15', 30', 45', 60',
and 90' rolls

THICKNESS

4.2 mils/105 microns

Capacity for high stretch and rebound. Has a soft hand and strong grip. Durable and weeds easily.
Pressure-sensitive carrier enables easy weeding and repositioning.

Special Precautions: This product cannot be layered.

Color Variation: During the manufacturing process, color variation can occur between rolls. This is especially true for Neon colors.

Tech Tips: For best results, perform test cuts.



CUTTING

45° Blade



PRESSING

Medium, even pressure



TIMING

15 seconds



WASHING

Wash warm, tumble dry normal. Suitable for dry-cleaning.



MIRRORING

Cut this material in mirror image.



TEMPERATURE

320-330°F



PEELING

Peel warm



LASER COMPATIBLE

This product contains no PVC and will not emit hazardous fumes.

"It's best to test!" Pre-test on an inconspicuous area before applying final production. Some garments require pre-heating and treatment, such as blotting moisture-wicking material with rubbing alcohol, before pressing material. Dye migration may occur with low energy dyes in polyester and blend fabrics. Check for compatibility and pre-treatment suggestions with each product's instructions. The user assumes all risk and liability, whatsoever, in connection with the use of this product. Specialty Materials cannot guarantee performance for conditions not under manufacturer's control and is not responsible for issues due to third-party material qualities. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

©2022 Specialty Materials & Digital Decoration, LLC. | All rights reserved | Tulsa, OK 74107 | 877-437-8556

Tech Help: tech@specialtymaterials.com | Sample Request: samples@specialtymaterials.com